



Connecting the World Now®  
[www.axestel.com](http://www.axestel.com)

## **MV600 Series**

CDMA 1xEV-DO Rev. B  
Wi-Fi Gateway



Connecting the World Now®  
www.axestel.com

### Features

- Backward compatible with CDMA2000 1xEV-DO Rev. 0/A and CDMA2000 1X
- VoIP and SIP Applications
- Up to 14.7Mbps for downlink / 5.4Mbps for uplink
- 802.11 b/g/n Wi-Fi Router with 4-Port Ethernet
- 5 LED Indicators (Power/Signal/Connect/1xEV-DO/Wi-Fi)
- Receive Diversity Antennas
- Optional Dual Mode HSPA+/Rev. B
- HSPA+ up to 14.4Mbps for downlink / 5.76Mbps for uplink
- Desktop or Wall Mountable
- TR-069
- IPv6 / IPv4
- Backup Battery Optional



## MV600 Series

### CDMA 1xEV-DO Rev. B Wi-Fi Gateway

The MV600 Series EV-DO Rev. B Gateways seamlessly combine wireless wide area networking (WWAN), a Wi-Fi wireless local area network (WLAN) router and a four port Ethernet switch to provide wireless broadband data access in one easy to use, plug-and-play desktop networking device. Leveraging CDMA2000 1xEV-DO Rev. B technology, the MV600 Series Gateways provide broadband data at speed up to 14.7 Mbps for high-speed access to email, the Internet, data intensive files and multi-media streaming. The integrated Wi-Fi router allows access to broadband data from any room at home or office and trouble-free set up of a local hotspot. A four port Ethernet switch provides a plug-and-play solution that enables users to network multiple desktop and laptop PCs as well as other devices.

### Specifications

- Operating Temperature: -20°C ~ +60°C
- Storage Temperature: -30°C ~ +70°C
- Humidity: 5 ~ 95%
- Size: 180 x 160 x 26 mm
- Weight: 500g
- Battery type: Li-ion (2 cell), 7.4V(Max 8.4V)/1000mA/h
- Stand by time: 1.5 ~ 2 hours
- Constant use time: 40 ~ 60 minutes
- Adaptor Input: 100/240V
- Adaptor Output: 9V/2A

### Benefits

- Integrated Wi-Fi router allows access to broadband data from anywhere at home or office
- Four-port Ethernet switch provides a plug-and-play solution for networking multiple desktops, laptops and other devices
- High-speed data with up to 14.7Mbps downlink and 5.4Mbps uplink
- Receive Diversity Antennas providing maximum coverage range and data throughput

### 3G Wireless Gateway

● : Standard   ○ : Not Available   ■ : Optional

Model	ML400 Series	MU430	MU530	MU700	MV400i Series	MV400 Series	MV500 Series	MV600 Series
Data	LTE / HSPA+	HSUPA	HSUPA	HSUPA	EV-DO Rev. A	EV-DO Rev. A	EV-DO Rev. A	EV-DO Rev. B / HSPA+
Ethernet Port	●	●	●	○	●	●	●	●
USB Port	○	●	(Printer / Storage)	●	●	●	●	○
Wi-Fi	●	●	●	●	○	●	●	●
Voice	○	○	●	○	○	○	■	■
RUIM/SIM	●	●	●	●	■	■	■	●
Frequency Band	LTE Band 13, 4, 17, 7, 3, 20, 1, 2	Tri Band (UMTS) Quad Band (GSM)	Tri Band (UMTS) Quad Band (GSM)	Tri Band (UMTS)	Single or Dual Band	Single or Dual Band	Single or Dual Band	Single Mode Rev. B 450MHz Single Mode HSPA+ Tri (UMTS) Quad (GSM) Dual Mode Rev. B 450MHz & HSPA+ 2100MHz
Backup Battery	●	●	○	●	■	■	●	■

The specifications and images of product herein are subject to change without notice by product definition and technical availability.